

Engineered Internationally specifically for South African Conditions



Cummins ISX 480 HP



+



Eaton Ultrashift Plus



/



ZF 12 Speed Astronic



Outstanding driving and handling characteristics, superb comfort and convenience that begins with spacious and comfortable cabin, powerful and rugged powertrain options, impressive hauling and carrying capabilities. Moreover it is built to handle around-the-clock high speed operations that will enhance your bottom line giving you lowest cost of ownership.

It's the obvious South African choice.

1 year/unlimited mileage on the complete vehicle. 3 years/600 000km on the drivetrain, whichever occurs first.

Ts & Cs apply



Maximus - KL3TX

Model	KL3TX - Eaton Gearbox	KL3TX - ZF Gearbox
ENGINE		
Make	Cummins	Cummins
Model	Cummins ISX 480	Cummins ISX 480
Capacity (cc)	14,946cc	14,946cc
Layout	Diesel inline 6 cylinders	Diesel inline 6 cylinders
Type	Turbo Intercooled	Turbo Intercooled
Power kw @r/min	354 @ 2,000	354 @ 2,000
Torque Nm @r/min	2,509 @ 1,200	2,509 @ 1,200
TRANSMISSION		
Make	Eaton Ultra Shift Plus	ZF Astronic
Model	FO-18E318B - AMT	ZF12AS2530TO
Type	Constant Mesh	Synchro Mesh
Shift	AMT	AMT
No. of gears fwd	18	12
MAJOR DIMENSIONS		
Overall height	3 405	3 395
Overall length (mm)	6 815	6 820
Overall width (mm)	2 570	2 570
Front overhang	1 465	1 465
Rear overhang	1 350	1 350
Wheelbase	3 890	3 890
CA -cab to bogie/rear axle	2 865	2 865
MASS		
GVM (kg)	25 500	25 500
V (kg)	25 500	25 500
GCM (kg)	75 000	75 000
D/T (kg)	75 000	75 000
Permissible body + payload (kg)	16 560	16 800
Unladen weight (kg)	8 940	8 700
Permissible rear axle weight (kg)	18 000	18 000
Permissible front axle weight	7 500	7 500
Manufacturer's rear axle weight (kg)	26 000	26 000
Manufacturer's front axle weight (kg)	7 500	7 500
CLUTCH		
Type	Twin	Single
Diameter (mm)	394mm	430mm
DRIVE AXLE		
Reduction Type	Single	Single
Finale ratio	4.444	4.111
BRAKES		
Type	Full Air Dual	Full Air Dual
Front	Drum	Drum
Rear	Drum	Drum
Anti-lock braking system	Standard	Standard
Auxiliary Engine brake	Standard	Standard
TYRES		
Size and ply rating	315/80R22.5	315/80R22.5
SUSPENSION		
Front & Rear	Multi Leaf Spring	Multi Leaf Spring
FUEL		
Fuel Tank 1 Capacity (ltrs)	400	400
Fuel Tank 2 Capacity (ltrs)	400	400

1) Accessories & Options Available
Bullbar & Spotlights, Aerokit, Alcoa Rims, Windscreen Protector & Others

2) Finance & Insurance Options Available
a) Retail / Installment
b) FML Contracts
c) Trade-ins and buy backs

***Dimensions & Weights are approximate

Tata Automobile Corporation SA (Pty) Ltd
Head Office: 011 255 9600

 Daewoo Trucks SA | www.daewootrucks.co.za

Dealer Stamp