

PRIMA 3338.K

THE WORLD SMART TRUCK



SPECIFICATIONS

VEHICLE WEIGHT (kg)

- Total Chassis Weight 11220
- Gross Vehicle Weight Rating (GVWR) 33000

VEHICLE DIMENSIONS (mm)

- Overall Length (OL) 8488
- Overall Width (OW) 2590
- Overall Height (OH) 3208
- Wheel Base (WB) 5250
- Front Overhang (FOH) 1482
- Rear Overhang (ROH) 1031
- Front Tread (FR Tr) 2038
- Rear Tread (RR Tr) 1900
- Ground Clearance 353

ENGINE

- Series Cummins ISLe 375
- Type Water cooled direct injection Turbocharged, after cooled Diesel Engine
- Max. Power PS/ rpm (JIS Gross) 375.3 / 2100
- Kgm/ rpm (JIS Gross) 158 / 1200-1400
- Nos.of Cylinders 6 inline
- Bore x Stroke (mm) 114 x 144.5
- Piston Displacement (cc) 8898
- Fuel System Direct Injection

CLUTCH

- Type Single Plate Dry Friction
- Disc Diameter (mm) 430

PERFORMANCE

- Max Speed (km/h) 66
- Grade ability tg θ (%) 54
- Grade ability tg θ (%) 83 (In Crawler Gear)

TRANSMISSION

- Series EATON ES154409
- No. of Speed 9 Speed Forward with Crawler + 1 Reverse
- Gear Ratio
 - 1st 10.040
 - 2nd 7.110
 - 3rd 5.050
 - 4th 3.710
 - 5th 2.710
 - 6th 1.920
 - 7th 1.360
 - 8th 1.000
 - Reverse 14.410
 - Crawler 14.390

FRONT AXLE

- Type Forged I beam Reverse Elliot

REAR AXLE

- Type TATA RA-210HR-T Planetary Hub Reduction, Fully Floating Axle Shafts
- Final Gear Ratio 7.246

STEERING

- Type Integral Hydraulic Power Assisted
- Min Turning Circle (m) 11.88 (at tyre)

BRAKES

- Main Control System Full Air Dual circuit - S Cam with ABS
- Front Brake drum 410x200 mm
- Rear Brake drum 410x220 mm
- Drum Inner Ø x Lining Width Front 4480 sq.cm
- Rear 4960 sq.cm
- Parking Hand operated - Air assisted spring

SUSPENSIONS

- Front Parabolic 16 Tons
- Span x Width (mm) 1600 x 90
- Optional specification is omitted Shock Absorber (and type) with (Hydraulic double acting telescopic) With
- Stabilizer
- Rear Two Spring balance beam Bogie with semi elliptic multi spring & rubber Mounted Torque Rods & V-rod Anti roll bar
- Optional specification is omitted. Shock Absorber (and type) with (Hydraulic double acting telescopic) With
- Stabilizer

WHEEL AND TYRE

- Wheel Disc Size 24 x 8.50
- Tyre Sizes 12.00 R24

ELECTRICAL EQUIPMENT

- Battery (V - Ah) (12 - 150) x 2
- Alternator (V - A) (28 - 90)

FUEL TANK

- Capacity (liters) 260

OTHER EQUIPMENTS

- Steering Column Tilt & Telescopic
- Radio/ Tape Available
- Air conditioning HVAC
- Other features Remote Key-Less entry, GPS, Immobilizer/Anti theft

PRIMA COMPETITIVE ADVANTAGE:

- Performa torsi tinggi (900 – 970 Nm) pada interval rpm yang panjang (1200 – 1700 rpm).
- Fitur keamanan yang lengkap (rem fuel air+ABS, area pandang luas dilengkapi lampu proyektor, side beam impact, retractable seat belt, collapsible steering).
- Total Cost Ownership (TCO) rendah.

PT TATA Motors Distribusi Indonesia

Pondok Indah Office Tower 3 Floor 8, Jl. Sultan Iskandar Muda Kav. V - TA,
Pondok Pinang - Jakarta Selatan 12310
Tel. +62-21-2932 8041/43, Fax. +62-21-2932 8042, Email: info@tatamotors.co.id

*Aksesoris dan poin peralatan opsional yang tertera pada ilustrasi dan fotografi bisa berbeda dengan spesifikasi standar. Warna kendaraan tergantung pada proses cetak dan bisa berbeda dengan gambar. Spesifikasi yang tertera bisa berubah sewaktu-waktu, tanpa pemberitahuan terlebih dahulu, tergantung kebijakan perusahaan dan pengembangan berkelanjutan.

Call Tata Motors (toll-free): 0-800-1-828200 Untuk informasi & ON-ROAD ASSISTANCE 24 JAM

www.tatamotors.co.id



TataMotorsID



@TataMotorsID



TatamotorsID



*Syarat dan ketentuan berlaku.
Mana yang tercapai terlebih dahulu.

Authorized Dealer: