



SFC 407 Ex TT



## Specifications

Engine type	Tata 4 SP turbo intercooled, water-cooled direct injection diesel engine
Engine capacity (cc)	2956
Max engine output	55.2 kW (75 Ps) at 2800 rpm
Max engine torque	225 Nm (22.9 mkg) at 1500 - 1800 rpm
Emission norms	Euro II
TRANSMISSION AND STEERING	i
Clutch	Single plate dry friction type
Gearbox	GBS-18 synchromesh (PTO-provision and PTO fitte optional), 5F +1R
Steering	Manual
SUSPENSION	
Front	Semi elliptical leaf spring
Rear	Semi elliptical leaf spring
Shock absorber	Hydraulic double acting telescopic type at front and rear
FRAME	
Туре	Ladder type frame with rivetted / bolted cross members, side members are of channel section, depth: 180 mm (max), width: 55 mm
BRAKE	
Service brake	Vacuum assisted dual circuit hydraulic with tandem master cylinder
WHEELS AND TYRES	
No.	6+1
Size	7.00R16-12PR - Radial tyres (Optional: 7.00 x 16-12PR diagonal ply)
Wheel base (mm)	3100
A / BE   BE   BE	

Overall length (mm)	5050
Max width (mm)	2006
WEIGHTS	
Kerb weight (Kg)	2025
GVW (Kg)	5300
PERFORMANCE	
Grade ability	22%
Top speed (kmph)	102
Minimum turning circle diameter in mm	12



## For more information, please contact:

TATA ZAMBIA LTD
LUSAKA:
PLOT NO. 9219 BEN BELLA ROAD
P.O BOX 30074 LUSAKA, ZAMBIA
Tel: +26 097 1245 397 Cell: +260 96 1931 498



TATA ZAMBIA LTD

NDOLA:
PLOT NO. 3025 AIRPORT ROAD
P.O BOX 71516 NDOLA, ZAMBIA

Tel: +26 097 1245 397 Cell: +260 96 6689 168

